



## MOTORI ELETTRICI CASSA IN GHISA - CAST IRON ELECTRIC MOTORS

### SERIE G TRIFASE 2 POLI - G SERIE THREEPHASE 2 POLES

Model	Power (kw)	Current (A)		Speed (r/min)	Eff (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Is/In (Times)	Noise dB(A)	W.t. (kg)
		380V	400V								
G 180M2A	22	41	39	2940	90.5	0.90	2.0	2.3	7.0	80	175
G 200L2A	30	55	52	2950	91.2	0.90	2.0	2.3	7.2	81	235
G 200L2B	37	68	65	2955	92.0	0.90	2.1	2.3	7.4	81	250
G 225M2A	45	82	78	2965	92.4	0.90	2.0	2.3	7.3	81	305
G 250M2A	55	100	95	2970	92.7	0.90	2.0	2.3	7.2	82	400
G 280S2A	75	134	127	2970	93.2	0.91	2.0	2.3	7.2	83	540
G 280M2A	90	160	152	2970	93.8	0.91	2.1	2.3	7.4	83	610
G 315S2A	11	195	185	2975	94.0	0.91	1.8	2.2	7.0	85	960
G 315M2A	132	233	222	2980	94.5	0.91	1.9	2.2	7.2	85	1050
G 315L2A	160	279	265	2980	94.8	0.92	1.9	2.2	7.2	86	1150
G 315L2B	200	350	333	2980	95.0	0.91	1.8	2.2	7.2	86	1200
G 355M2A	250	435	415	2983	95.3	0.92	1.6	2.2	7.0	88	1750
G 355L2A	315	545	520	2985	95.6	0.92	1.6	2.2	7.2	88	1850

Motori elettrici conformi alle normative CE, standard IEC; protezione IP55, isolamento F, servizio S1, Eff2

Electric motors CE conform, standard IEC; protection IP55, insulation F, Duty S1, Eff2