



## MOTORI ELETTRICI CASSA IN GHISA - CAST IRON ELECTRIC MOTORS

### SERIE G TRIFASE 4 POLI - G SERIE THREEPHASE 4 POLES

Model	Power (kw)	Current (A)		Speed (r/min)	Eff (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Is/In (Times)	Noise dB(A)	W.t. (kg)
		380V	400V								
G 180M4A	18.5	36.5	35	1470	90.7	0.85	2.0	2.3	7.0	69	180
G 180L4A	22	43	41	1470	91.3	0.85	2.2	2.3	7.2	69	190
G 200L4A	30	57	54	1475	92.2	0.86	2.0	2.3	7.0	70	260
G 225S4A	37	69.5	66	1480	92.6	0.87	2.0	2.3	7.0	72	285
G 225M4A	45	84	80	1480	92.9	0.87	2.2	2.3	7.2	72	320
G 250M4A	55	102	97	1480	93.3	0.87	2.1	2.3	7.0	74	410
G 280S4A	75	139	132	1485	93.9	0.87	2.0	2.3	7.0	76	550
G 280M4A	90	165	158	1485	94.3	0.87	2.2	2.3	7.0	76	650
G 315S4A	110	200	190	1490	94.5	0.88	2.1	2.2	6.7	81	1000
G 315M4A	132	240	230	1490	94.8	0.88	2.1	2.3	6.8	81	1100
G 315L4A	160	285	270	1490	95.1	0.89	2.2	2.3	6.9	84	1160
G 315L4B	200	355	340	1490	95.3	0.89	2.2	2.3	6.9	85	1270
G 355M4A	250	440	420	1492	95.5	0.90	2.0	2.2	6.5	87	1700
G 355L4A	315	555	530	1493	95.7	0.90	2.1	2.3	6.7	87	1850

Motori elettrici conformi alle normative CE, standard IEC; protezione IP55, isolamento F, servizio S1, Eff2

Electric motors CE conform, standard IEC; protection IP55, insulation F, Duty S1, Eff2