



MOTORI ELETTRICI CASSA IN GHISA - CAST IRON ELECTRIC MOTORS

SERIE G TRIFASE 6 POLI - G SERIE THREEPHASE 6 POLES

Model	Power (kw)	Current (A)		Speed (r/min)	Eff (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Is/In (Times)	Noise dB(A)	W.t. (kg)
		380V	400V								
G 180L6A	15	31	29.5	975	89.3	0.81	2.1	2.2	6.6	68	185
G 200L6A	18.5	37.5	35.5	975	90.1	0.82	2.0	2.1	6.6	68	215
G 200L6B	22	44	42	975	90.3	0.83	2.1	2.2	6.8	68	245
G 225M6A	30	58	55	980	91.5	0.84	2.1	2.2	6.7	69	290
G 250M6A	37	79	68	980	92.0	0.86	2.1	2.2	6.7	70	395
G 280S6A	45	85	81	983	92.7	0.86	2.0	2.1	6.6	72	515
G 280M6A	55	104	99	985	93.0	0.86	2.1	2.2	6.8	72	580
G 315S6A	75	140	135	990	93.7	0.86	2.0	2.9	6.7	75	960
G 315M6A	90	168	160	990	94.0	0.86	2.0	2.2	6.8	75	1050
G 315L6A	110	205	195	992	94.3	0.86	1.9	2.0	6.5	77	1130
G 315L6B	132	244	235	992	94.4	0.87	1.9	2.0	6.6	77	1200
G 355M6A	160	290	275	993	94.7	0.88	1.8	2.1	6.5	80	155
G 355M6B	200	360	345	993	95.0	0.88	1.9	2.1	6.6	80	1680
G 355L6A	250	450	430	993	95.3	0.88	1.9	2.1	6.8	82	1800

Motori elettrici conformi alle normative CE, standard IEC; protezione IP55, isolamento F, servizio S1, Eff2

Electric motors CE conform, standard IEC; protection IP55, insulation F, Duty S1, Eff2