



MOTORI ELETTRICI CASSA IN GHISA - CAST IRON ELECTRIC MOTORS

SERIE G TRIFASE 8 POLI - G SERIE THREEPHASE 8 POLES

Model	Power (kw)	Current (A)		Speed (r/min)	Eff (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Is/In (Times)	Noise dB(A)	W.t. (kg)
		380V	400V								
G 180L8A	11	25	24	730	87.6	0.77	2.0	2.1	6.3	65	180
G 200L8A	15	34	32.5	735	88.2	0.77	1.9	2.0	6.3	67	245
G 225S8A	18,5	40	38.5	735	90.0	0.78	1.9	2.0	6.3	68	265
G 225M8A	22	47	45	740	90.5	0.79	2.0	2.1	6.5	68	290
G 250M8A	30	62	59.5	740	91.2	0.80	1.9	2.1	6.3	69	395
G 280S8A	37	76	73	740	91.7	0.80	1.9	2.1	6.4	70	510
G 280M8A	45	92	88	742	92.2	0.80	2.0	2.1	6.5	70	580
G 315S8A	55	112	108	742	92.9	0.82	1.8	2.0	6.3	73	960
G 315M8A	75	150	145	743	93.2	0.82	1.8	2.1	6.4	73	1060
G 315L8A	90	176	169	743	93.9	0.83	1.8	2.1	6.4	75	1130
G 315L8B	110	215	206	743	94.2	0.83	1.8	2.1	6.4	75	1200
G 355M8A	132	260	250	745	94.0	0.83	1.7	2.0	6.2	78	1600
G 355M8B	160	310	290	745	94.3	0.83	1.8	2.1	6.4	78	1700
G 355L8A	200	385	370	745	94.6	0.84	1.8	2.1	6.4	80	1800

Motori elettrici conformi alle normative CE, standard IEC; protezione IP55, isolamento F, servizio S1, Eff2

Electric motors CE conform, standard IEC; protection IP55, insulation F, Duty S1, Eff2