



MOTORI ELETTRICI CASSA IN ALLUMINIO - ALUMINIUM HOUSING ELECTRIC MOTORS

SERIE MG2 TRIFASE 6 POLI - MG2 SERIE THREEPHASE 6 POLES

Model	Power (kw)	Current (A)			Speed (r/min)	Eff (%)	Power factor	Tstart/Tn (Times)	Tmax/Tn (Times)	Is/In (Times)	Noise dB(A)	W.t. (kg)
		230V	400V	690V								
63 6A	0,09	0.88	0.51	0.29	840	42	0,61	2	2	3,5	50	4,20
63 6B	0,12	1.08	0.62	0.36	850	45	0,62	2	2	3,5	50	4,80
71 6A	0,18	1.22	0.70	0.41	880	56	0,66	1,6	1,7	4	52	6,00
71 6B	0,25	1.51	0.87	0.50	900	59	0,7	2,1	2,2	4	52	6,50
71 6C	0,37	2.2	1.27	0.73	890	61	0,69	2	2,1	4	54	7,20
80 6A	0,37	2.13	1.23	0.71	900	62	0,7	1,9	1,9	4	56	8,20
80 6A	0,55	2.85	1.65	0.95	900	67	0,72	2	2,3	4	56	9,90
80 6C	0,75	3.83	2.21	1.28	900	68	0,72	2	2,3	4	58	11,30
90S6A	0,75	3.77	2.18	1.26	920	69	0,72	2,2	2,2	5,5	59	11,70
90L6B	1,1	5.23	3.02	1.74	925	72	0,73	2,2	2,2	5,5	59	15,10
100L6A	1,5	6.67	3.85	2.22	945	74	0,76	2,2	2,2	6	61	19,10
112M6A	2,2	9.28	5.36	3.09	955	78	0,76	2,2	2,2	6	64	25,40
132S6A	3	12.49	7.21	4.16	960	79	0,76	2	2	6,5	64	36,10
132M6B	4	16.35	9.44	5.45	960	80,5	0,76	2	2	6,5	68	45,00
132M6C	5,5	21.51	12.42	7.17	960	83	0,77	2	2	6,5	68	55,50
132L6D	7,5	28.65	16.54	9.55	960	85	0,77	2	2	6,5	68	60,00
160M6A	7,5	27.25	15.73	9.08	960	86	0,8	2	2,2	6,5	68	72,00
160L6B	11	39.78	22.97	13.26	960	87,5	0,79	2	2,2	6,5	73	92,00

Motori elettrici conformi alle normative CE, standard IEC; protezione IP55, isolamento F-H, servizio S1, Eff2  
 Electric motors CE conform, standard IEC; protection IP55, insulation F-H, Duty S1, Eff2